

SIMULTANEOUS MULTI CONNECTION
AIR CONDITIONER
(50Hz)

SERVICE MANUAL



CONTENTS

SPECIFICATIONS	1
DIMENSIONS	7
REFRIGERANT SYSTEM DIAGRAM . . .	12
CIRCUIT DIAGRAM	14
PCB CIRCUIT DIAGRAM	17
ERROR DETECTION	22
PARTS (OUTDOOR UNIT)	24
PARTS (INDOOR UNIT)	28
ACCESSORIES	49

Outdoor unit	Indoor unit
AOYG36LBTB	ABYG18LVTB
UTP-SX236A	ARYG18LLTB
	AUYG18LVLB
	UTG-UFYD-W
AOYG45LBTB	ABYG22LVTA
UTP-SX254A	ARYG22LMLA
	AUYG22LVLA
	UTG-UFYD-W
AOYG54LBTB	ABYG18LVTB
UTP-SX254A	ABYG24LVTA
UTP-SX354A	ARYG18LLTB
	ARYG24LMLA
	AUYG18LVLB
	AUYG24LVLA
	UTG-UFYD-W

SPECIFICATIONS

ELECTRICAL DATA

Model name		AOYG36LBTB ABYG18LVTV x 2	AOYG36LBTB ARYG18LLTB x 2	AOYG36LBTB AUYG18LVLB x 2
Power supply		Single phase 230V 50Hz		
Cooling	Capacity	10.0 kW	10.0 kW	10.0 kW
	Power consumption	2.89 kW	2.86 kW	2.89 kW
	EER	3.46 kW/kW	3.50 kW/kW	3.46 kW/kW
	Rated operating current	12.8 A	12.7 A	12.8 A
	Max operating current	19.0 A	19.0 A	19.0 A
Heating	Capacity	11.2 kW	11.2 kW	11.2 kW
	Power consumption	3.06 kW	2.89 kW	3.06 kW
	COP	3.66 kW/kW	3.87 kW/kW	3.66 kW/kW
	Rated operating current	13.6 A	12.8 A	13.6 A
	Max operating current	19.0 A	19.0 A	19.0 A

Model name		AOYG45LBTB ABYG22LVTA x 2	AOYG45LBTB ARYG22LMLA x 2	AOYG45LBTB AUYG22LVLA x 2
Power supply		Single phase 230V 50Hz		
Cooling	Capacity	12.1 kW	12.1 kW	12.1 kW
	Power consumption	3.77 kW	3.70 kW	3.77 kW
	EER	3.21 kW/kW	3.27 kW/kW	3.21 kW/kW
	Rated operating current	16.7 A	16.4 A	16.7 A
	Max operating current	20.4 A	20.4 A	20.4 A
Heating	Capacity	14.0 kW	14.0 kW	14.0 kW
	Power consumption	3.97 kW	3.93 kW	3.97 kW
	COP	3.52 kW/kW	3.56 kW/kW	3.52 kW/kW
	Rated operating current	17.6 A	17.4 A	17.6 A
	Max operating current	20.4 A	20.4 A	20.4 A

ELECTRICAL DATA

Model name		AOYG54LBTB ABYG24LVTA x 2	AOYG54LBTB ABYG18LVTB x 3	AOYG54LBTB ARYG24LMLA x 2	AOYG54LBTB ARYG18LLTB x 3	AOYG54LBTB AUYG24LVLA x 2	AOYG54LBTB AUYG18LVLB x 3
Power supply		Single phase 230V 50Hz					
Cooling	Capacity	13.3 kW	13.3 kW	13.3 kW	13.3 kW	13.3 kW	13.3 kW
	Power consumption	4.40 kW	4.23 kW	4.40 kW	4.14 kW	4.40 kW	4.23 kW
	EER	3.02 kW/kW	3.14 kW/kW	3.02 kW/kW	3.21 kW/kW	3.02 kW/kW	3.14 kW/kW
	Rated operating current	19.5 A	18.8 A	19.5 A	18.4 A	19.5 A	18.8 A
	Max operating current	21.5 A	21.5 A	21.5 A	21.5 A	21.5 A	21.5 A
Heating	Capacity	15.0 kW	16.0 kW	15.0 kW	16.0 kW	15.0 kW	16.0 kW
	Power consumption	4.48 kW	4.53 kW	4.40 kW	4.34 kW	4.48 kW	4.53 kW
	COP	3.35 kW/kW	3.53 kW/kW	3.41 kW/kW	3.68 kW/kW	3.35 kW/kW	3.53 kW/kW
	Rated operating current	19.9 A	20.1 A	19.5 A	19.3 A	19.9 A	20.1 A
	Max operating current	21.5 A	21.5 A	21.5 A	21.5 A	21.5 A	21.5 A

OUTDOOR UNIT

FAN MOTOR AND FAN REVOLUTION

Model name		AOYG36LBTB	AOYG45LBTB		AOYG54LBTB
Connection			AB AU	AR	
Discrimination		MFE-45VVT			
Cooling	Upper fan	780 rpm	850 rpm		900 rpm
	Lower fan	750 rpm	800 rpm		800 rpm
Heating	Upper fan	780 rpm	780	850	850 rpm
	Lower fan	750 rpm	750	830	830 rpm

AIR CIRCULATION

Cooling	6,200 m3/h	6,750 m3/h		6,850 m3/h
Heating	6,200 m3/h	6,200	6,750	6,750 m3/h

NOISE LEVEL

Cooling	52 dB	54 dB		55 dB
Heating	54 dB	55 dB	56 dB	57 dB

COMPRESSOR AND REFRIGERANT

Type		Hermetic type, Inverter, 4 poles, DC motor, Twin Rotary	
Discrimination*	A	DA422A3F-28ZAD	
	B	DA422A3T-20ZA	
Weight (with oil)	A	23.0 kg	
	B	23.3 kg	
Refrigerant type		R410A	
Precharged refrigerant		3,450 g	
Total pipe length	30 m	3,450 g	
	45 m	4,200 g	
	60 m	4,950 g	
	75 m	5,700 g	
Additional charge		50 g/m	

*B is interchangeable with A.

MEASUREMENT

Dimensions H x W x D	1,290 x 900 x 330 mm
Weight Net / Shipping	93 kg / 102 kg

INDOOR UNIT CEILING TYPE

FAN MOTOR AND FAN REVOLUTION

Model name		ABYG18LVTB	ABYG22LVTA	ABYG24LVTA
Discrimination		MFH-24RVL		
Cooling	High	1,040 rpm	1,330 rpm	
	Medium	950 rpm	1,150 rpm	
	Low	800 rpm	1,000 rpm	
	Quiet	740 rpm	780 rpm	
Heating	High	1,040 rpm	1,300 rpm	
	Medium	950 rpm	1,150 rpm	
	Low	800 rpm	1,000 rpm	
	Quiet	740 rpm	780 rpm	

AIR CIRCULATION

Ventilation	High	780 m3/h	980 m3/h
	Medium	700 m3/h	820 m3/h
	Low	560 m3/h	680 m3/h
	Quiet	500 m3/h	540 m3/h

NOISE LEVEL

Cooling	High	43 dB	48 dB
	Medium	40 dB	44 dB
	Low	34 dB	40 dB
Heating	Quiet	31 dB	35 dB
	High	43 dB	48 dB
	Medium	40 dB	44 dB
	Low	34 dB	40 dB
	Quiet	31 dB	35 dB

MEASUREMENT

DIMENSIONS	H x W x D	199 x 990 x 655 mm
WEIGHT	Net / Shipping	27 kg / 36 kg

INDOOR UNIT DUCT TYPE

FAN MOTOR AND FAN REVOLUTION

Model name		ARYG18LLTB	ARYG22LMLA	ARYG24LMLA
Discrimination		MFG-24WVAL	MFG-24RVAL	
Cooling	High	1,380 rpm	830 rpm	
	Medium	1,300 rpm	700 rpm	
	Low	1,220 rpm	600 rpm	
	Quiet	1,140 rpm	550 rpm	
Heating	High	1,380 rpm	830 rpm	
	Medium	1,300 rpm	700 rpm	
	Low	1,220 rpm	600 rpm	
	Quiet	1,140 rpm	550 rpm	

AIR CIRCULATION

Ventilation	High	940 m3/h	1,100 m3/h
	Medium	880 m3/h	910 m3/h
	Low	820 m3/h	750 m3/h
	Quiet	750 m3/h	580 m3/h

NOISE LEVEL

Cooling	High	32 dB	31 dB
	Medium	30 dB	29 dB
	Low	29 dB	27 dB
	Quiet	27 dB	25 dB
Heating	High	32 dB	31 dB
	Medium	30 dB	29 dB
	Low	29 dB	27 dB
	Quiet	27 dB	25 dB

MEASUREMENT

DIMENSIONS	H x W x D	198 x 900 x 620	270 x 1,135 x 700 mm
WEIGHT	Net / Shipping	23 kg / 30 kg	38 kg / 44 kg

INDOOR UNIT CASSETTE TYPE

FAN MOTOR AND FAN REVOLUTION

Model name		AUYG18LVLB	AUYG22LVLA	AUYG24LVLA
Discrimination		MFF-24RVL		
Cooling	High	730 rpm	960 rpm	
	Medium	630 rpm	850 rpm	
	Low	540 rpm	650 rpm	
	Quiet	460 rpm	500 rpm	
Heating	High	830 rpm	960 rpm	
	Medium	730 rpm	880 rpm	
	Low	630 rpm	740 rpm	
	Quiet	500 rpm	580 rpm	

AIR CIRCULATION

Ventilation	High	680 m3/h	930 m3/h
	Medium	580 m3/h	830 m3/h
	Low	490 m3/h	600 m3/h
	Quiet	410 m3/h	450 m3/h

NOISE LEVEL

Cooling	High	38 dB	49 dB
	Medium	34 dB	44 dB
	Low	30 dB	36 dB
	Quiet	26 dB	30 dB
Heating	High	43 dB	49 dB
	Medium	38 dB	45 dB
	Low	34 dB	40 dB
	Quiet	30 dB	33 dB

MEASUREMENT

DIMENSIONS	H x W x D	245 x 570 x 570 mm	
WEIGHT	Net / Shipping	15 kg / 18 kg	16 kg / 19 kg


DECORATION PANL MEASUREMENT

DIMENSIONS	H x W x D	49 x 700 x 700 mm	
WEIGHT	Net / Shipping	2.6 kg / 4.5 kg	

DIMENSIONS



OUTDOOR UNIT

Unit : mm





BRANCH PIPE
(unit : mm)



UTP-SX236A





Liquid pipe





UTP-SX254A





Liquid pipe





UTP-SX354A




Liquid pipe





INDOOR UNIT
CEILING
ABYG18LVTB
ABYG22LVTA
ABYG24LVTA
Unit : mm






INDOOR UNIT
SLIM DUCT
ARYG18LLTB
Unit : mm




INDOOR UNIT
DUCT
ARYG22LMLA
ARYG24LMLA
Unit : mm




INDOOR UNIT
CASSETTE
AUYG18LVLB
AUYG22LVLA
AUYG24LVLA
Unit : mm

INDOOR UNIT



DECORATION PANEL
UTG-UFYD-W




REFRIGERANT SYSTEM DIAGRAM

Refrigerant flow


—→ : Cool

---→ : Heat

OUTDOOR UNIT




INDOOR UNIT



LIMITATION OF PIPE CONNECTION

Two indoor units



Maximum length of total pipe

$$L1 + L2 + L3 = 75\text{m}$$

Maximum length of branch piping

$$L2 = 20\text{m} \quad L3 = 20\text{m}$$


Maximum height between indoor and outdoor units

$$H1 = 30\text{m}$$

Maximum height between indoor units

$$H2 = 0.5\text{m}$$

Three indoor units



Maximum length of total pipe

$$L1 + L2 + L3 + L4 = 75\text{m}$$

Maximum length of branch piping

$$L2 = 20\text{m} \quad L3 = 20\text{m} \quad L4 = 20\text{m}$$

Maximum height between indoor and outdoor units


$$H1 = 30\text{m}$$

Maximum height between indoor units


$$H2 = 0.5\text{m}$$

CIRCUIT DIAGRAM


OUTDOOR UNIT
AOYG36LBTB
AOYG45LBTB
AOYG54LBTB




Models : ABYG18LVTB
 ABYG22LVTA
 ABYG24LVTA




Model : ARYG18LLTB



Models : ARYG22LMLA
ARYG24LMLA




Models : AUYG18LVLB
AUYG22LVLA
AUYG24LVLA
UTG-UFYD-W



OUTDOOR UNIT

AOYG54LBTA: EZ-0150AHUE



Thermistor	Temperature	0 °C	20 °C	30 °C
CN61 Thermistor (Outdoor temp.)		35.2 k Ω 2.6 V	12.6 k Ω 3.8 V	8.0 k Ω 4.1 V
CN62 Thermistor (Discharge temp.) Thermistor (Comp. temp.)		168.6 k Ω 0.4 V	62.6 k Ω 0.9 V	40.0 k Ω 1.2 V
CN63 Thermistor (Pipe mid. temp.) Thermistor (Pipe temp.)		16.1 k Ω 1.1 V	6.0 k Ω 2.2 V	3.8 k Ω 2.8 V

FLASH (MAIN)


FLASH (I NV)

CN5
B06B-PASK-1
WHITE DC5

CN350
B06B-PAKK-1
BLACK DC


INDOOR UNIT
CEILING

CONTROL UNIT
ABYG18LVTB : EZ-0122BHSE
ABYG22LVTA : EZ-0122YHSE
ABYG24LVTA : EZ-0122CHSE



CN105 DC Fan motor

Pin No.	Terminal code	Function of terminal	Lead wire color
6	Vm	Motor power voltage input	Red
5	—	—	—
4	GND	GND	Black
3	Vcc	Control power voltage input	White
2	Vsp	Speed control voltage input	Yellow
1	FG	Revolution pulse output	Brown



CN8 Thermistor Characteristics.


Thermistor	Temperature (0℃)	(20℃)	(30℃)
Thermistor (Room temp.)	33.6 k Ω 1.1 V	12.5 k Ω 2.2 V	8.0 k Ω 2.8 V

CN5 Thermistor Characteristics.


Thermistor	Temperature (0℃)	(20℃)	(30℃)
Thermistor (Pipe temp.)	176.0 k Ω 1.1 V	62.9 k Ω 2.2 V	39.6 k Ω 2.8 V

INDOOR UNIT
DUCT
ARYG18LLTB

CONTROL UNIT
EZ-01226HSE




Pin No.	Terminal code	Function of terminal	Lead wire color
6	Vm	Motor power voltage input	Red
5			
4	GND	GND	Black
3	Voc	Control power voltage input	White
2	Vsp	Speed control voltage input	Yellow
1	PG	Revolution pulse output	Blue



INDOOR UNIT
DUCT

CONTROL UNIT
ARYG22LMLA : EZ-01226HSE
ARYG24LMLA : EZ-01227HSE



CN8 Thermistor Characteristics.


Thermistor	Temperature	0 °C	20 °C	30 °C
Thermistor (room temp.)		33.6 k Ω 1.1 V	12.5 k Ω 2.2 V	8.0 k Ω 2.8 V

CN5 Thermistor Characteristics.

Thermistor	Temperature	0 °C	20 °C	30 °C
Thermistor (Pipe temp.)		176.0 k Ω 1.1 V	62.9 k Ω 2.2 V	39.6 k Ω 2.8 V

INDOOR UNIT
CASSETTE


CONTROL UNIT
AUYG18LVLB : EZ-0122LHSE
AUYG22LVLA : EZ-01230HSE
AUYG24LVLA : EZ-0122MHSE



ERROR DETECTION

OUTDOOR UNIT ERROR CODE DISPLAY

You can determine the operating status by the lighting up and blinking of the LED lamp.



Display when an error occurs

POWER	ERROR	PUMP DOWN	LOW NOISE			PEAK CUT	
MODE		(L1)	(L2)	(L3)	(L4)	(L5)	(L6)
●	Blink (Hi speed)	○	○	○	○	○	○

Sign "○": Lights off, "●": Lights on

- (1) Check that the "ERROR" LED blinks, then press the [Enter] button once.
- (2) For details, refer to the following table.


Display mode ● : ON
○ : OFF
◆ : Blink (0.5s ON / 0.5s OFF)
() : Number of flashing

Error code check table


LED display								DESCRIPTION	REMARK
POWER MODE	ERROR	PUMP DOWN	LOW NOISE		PEAK CUT				
		(L1)	(L2)	(L3)	(L4)	(L5)	(L6)		
◆(2)	●	◆(1)	◆(1)	○	○	●	●	Serial communication error	Serial forward transmission error immediately after operation
◆(2)	●	◆(1)	◆(1)	○	●	○	○		Serial forward transmission error during operation
◆(2)	●	◆(2)	◆(2)	○	○	○	●	Indoor unit capacity error	Indoor unit capacity error
◆(2)	●	◆(5)	◆(15)	○	○	○	●	Indoor unit error	Indoor unit error
◆(2)	●	◆(6)	◆(2)	○	○	○	●	Outdoor unit main PCB error	Outdoor unit PCB model information error
◆(2)	●	◆(6)	◆(3)	○	○	○	●	Inverter PCB error	Inverter error
◆(2)	●	◆(6)	◆(5)	○	○	●	●	IPM error	Trip terminal L error
◆(2)	●	◆(7)	◆(1)	○	○	○	●	Discharge temp. sensor error	Discharge temp. sensor 1 error
◆(2)	●	◆(7)	◆(2)	○	○	○	●	Compressor temp. sensor error	Compressor temp. sensor 1 error
◆(2)	●	◆(7)	◆(3)	○	○	●	○	Outdoor unit Heat Ex. sensor error	Heat Ex. middle temp. sensor error
◆(2)	●	◆(7)	◆(3)	○	○	●	●		Outdoor unit Heat Ex. liquid temp. sensor error
◆(2)	●	◆(7)	◆(4)	○	○	○	●	Outdoor temp. sensor error	Outdoor temp. sensor error
◆(2)	●	◆(7)	◆(7)	○	○	○	●	Heat sink temp. sensor error	Heat sink temp. sensor error
◆(2)	●	◆(8)	◆(4)	○	○	○	●	Current sensor error	Current sensor 1 error (stoppage permanently)
◆(2)	●	◆(8)	◆(6)	○	●	○	○	Pressure sensor error	High pressure switch 1 error
◆(2)	●	◆(8)	◆(6)	○	●	●	○		Pressure sensor error
◆(2)	●	◆(9)	◆(4)	○	○	○	●	Trip detection	Trip detection
◆(2)	●	◆(9)	◆(5)	○	○	○	●	Compressor motor control error	Rotor position detection error (stoppage permanently)
◆(2)	●	◆(9)	◆(7)	○	○	●	●	Outdoor unit fan motor 1 error	Duty error
◆(2)	●	◆(9)	◆(8)	○	○	●	●	Outdoor unit fan motor 2 error	Duty error
◆(2)	●	◆(9)	◆(9)	○	○	○	●	4-way valve error	4-way valve error
◆(2)	●	◆(10)	◆(1)	○	○	○	●	Discharge temp. 1 error	Discharge temp. 1 error
◆(2)	●	◆(10)	◆(3)	○	○	○	●	Compressor temp. error	Compressor 1 temp. error
◆(2)	●	◆(10)	◆(5)	○	○	○	●	Pressure error 2	Low pressure error

WIRED REMOTE CONTROL


This is possible only on a wired remote control.
 If an error occurs, the following display will be shown.
 (“Er” will appear in the set room temperature display.)



INDOOR UNIT (CEILING)




INDOOR UNIT (CASSETTE)



- : 0.5s on / 0.5s off
- ◇ : 0.1s on / 0.1s off
- () : Number of flashing

Indoor unit			Wired remote control	Description
OPERATION lamp (green)	TIMER lamp (orange)	ECONOMY lamp (green)		
● (1)	● (1)	◇	11	Serial communication error
● (1)	● (2)	◇	12	Wired remote control communication error
● (1)	● (5)	◇	15	Check run unfinished
● (2)	● (1)	◇	21	Unit number or Refrigerant circuit address setting error [Simultaneous Multi]
● (2)	● (2)	◇	22	Indoor unit capacity error
● (2)	● (3)	◇	23	Combination error
● (2)	● (4)	◇	24	• Connection unit number error (indoor slave unit) [Simultaneous Multi] • Connection unit number error (indoor unit or branch unit) [Flexible Multi]
● (2)	● (7)	◇	27	Master unit, slave unit set-up error [Simultaneous Multi]
● (3)	● (1)	◇	31	Power supply interruption error
● (3)	● (2)	◇	32	Indoor unit PCB model information error
● (3)	● (5)	◇	35	Manual auto switch error
● (4)	● (1)	◇	41	Inlet air temp. sensor error
● (4)	● (2)	◇	42	Indoor unit Heat Ex. Middle temp. sensor error
● (5)	● (1)	◇	51	Indoor unit fan motor error
● (5)	● (3)	◇	53	Drain pump error
● (5)	● (7)	◇	57	Damper error
● (5)	● (15)	◇	5U	Indoor unit error
● (6)	● (2)	◇	62	Outdoor unit main PCB model information error or communication error
● (6)	● (3)	◇	63	Inverter error
● (6)	● (4)	◇	64	Active filter error, PFC circuit error
● (6)	● (5)	◇	65	Trip terminal L error
● (6)	● (10)	◇	6A	Display PCB microcomputers communication error

Indoor unit			Wired remote control	Description
OPERATION lamp (green)	TIMER lamp (orange)	ECONOMY lamp (green)		
● (7)	● (1)	◇	71	Discharge temp. sensor error
● (7)	● (2)	◇	72	Compressor temp. sensor error
● (7)	● (3)	◇	73	Outdoor unit Heat Ex. liquid temp. sensor error
● (7)	● (4)	◇	74	Outdoor temp. sensor error
● (7)	● (5)	◇	75	Suction Gas temp. sensor error
● (7)	● (6)	◇	76	• 2-way valve temp. sensor error • 3-way valve temp. sensor error
● (7)	● (7)	◇	77	Heat sink temp. sensor error
● (8)	● (2)	◇	82	• Sub-cool Heat Ex. gas inlet temp. sensor error • Sub-cool Heat Ex. gas outlet temp. sensor error
● (8)	● (3)	◇	83	Liquid pipe temp. sensor error
● (8)	● (4)	◇	84	Current sensor error
● (8)	● (6)	◇	86	• Discharge pressure sensor error • Suction pressure sensor error • High pressure switch error
● (9)	● (4)	◇	94	Trip detection
● (9)	● (5)	◇	95	Compressor rotor position detection error (permanent stop)
● (9)	● (7)	◇	97	Outdoor unit fan motor 1 error
● (9)	● (8)	◇	98	Outdoor unit fan motor 2 error
● (9)	● (9)	◇	99	4-way valve error
● (9)	● (10)	◇	9A	Coil (expansion valve) error
● (10)	● (1)	◇	A1	Discharge temp. error
● (10)	● (3)	◇	A3	Compressor temp. error
● (10)	● (4)	◇	A4	High pressure error
● (10)	● (5)	◇	A5	Low pressure error
● (13)	● (2)	◇	J2	Branch boxes error [Flexible Multi]




PARTS



OUTDOOR UNIT
 AOYG36LBTB
 AOYG45LBTB
 AOYG54LBTB

Ref.	Description	Parts number	
1	Drain Assy	9303029015	
2	Drain Cap	313166024302	
3	Protective Net	9375381042	
4	Thermo Holder	9375211011	
5	Top Panel Sub Assy	9374417056	
6	Front Panel Sub Assy	9374414154	
7	Service Panel Sub Assy	9374415090	
8	Emblem Rear	9351355005	
9	Pipe Cover Front	9378861015	
10	Right Panel Sub Assy	9374416264	
11	DC Fan Motor	9602843039	
12	Propeller Fan Assy	9366378020	
13	Outdoor Thermistor	9900210069	

OUTDOOR UNIT
AOYG36LBTB
AOYG45LBTB
AOYG54LBTB
Control box




Ref.	Description	Parts number
21	Main PCB (36)	9709904305
21	Main PCB (45)	9709904312
21	Main PCB (54)	9709904329
22	Indicator PCB	9708678016
24	Terminal	9900428020
25	Filter PCB	9709903070
26	Thermistor	9704265012
27	Capacitor PCB	9709894101
28	Choke Coil	9900624019
29	ACTPM	9707592016
30	Transistor PCB	9709682906
31	Heat Sink	9380358008



OUTDOOR UNIT
AOYG36LBTB
AOYG45LBTB
AOYG54LBTB


Ref.	Description	Parts number	
61	Thermistor Assy (5 pins)	9900599027	
62	Thermistor Assy (4 pins)	9900598013	
63	Condenser A Sub Assy	9374420261	
64	Condenser B Sub Assy	9374422081	
65	Bypass Pipe A	9371324043	
66	Expansion Valve Coil	9970098062	
67	Expansion Valve Assy	9370947182	
68	3-way Valve Assy	9379077002	
69	3-way Valve Assy	9379079006	
70	Solenoid	9970113055	
71	4-way Valve Assy	9374425273	
72	Sensor	9900505080	
73	Accumulator Assy	9375250096	
74*	Compressor Sub Assy	9383161001	A
74*	Compressor Sub Assy	9374423460	B

Ref.74 : B is interchangeable with A, When there is no stock
A, B is shipped automatically.




PARTS


BRANCH PIPE
UTP-SX236A



UTP-SX254A




UTP-SX354A



Ref.	Description	Parts number	
1	Branch Pipe A Assy	9379090018	
2	Branch Pipe B Assy	9379096010	
3	Branch Pipe A Assy	9379102018	
4	Branch Pipe B Assy	9379105019	
5	Insulation A	9379100014	
6	Insulation B	9379101011	
7	Branch Pipe A Assy	9379116015	
8	Branch Header B Assy	9379108010	
9	Insulation A	9379111010	
10	Insulation B	9379112017	


PARTS

INDOOR UNIT
CEILING
ABYG18LVTB
ABYG22LVTA
ABYG24LVTA



Ref.	Description	Part number	
1	Remote Control	9379219037	
2	Remote Control Holder	9305642045	
3	Cosmetic Panel R	9358535028	
4	Cosmetic Panel L	9358536025	
5	Top Cover	9358534021	
6	Kit (Grill Sub Assy)	9372676035	
7	Air Filter	9358567036	
8	Panel Assy	9359076322	
9	Panel Sub Assy	9359057239	


INDOOR UNIT
CEILING
ABYG18LVTB
ABYG22LVTA
ABYG24LVTA
Flap base assy





Ref.	Description	Part number	
11	Flap (Upper) F	9358538029	
12	Kit (Flap Lower)	9372671023	
13	Bushing	9357942001	
14	Bushing C	9358553008	
15	Step Motor H	9900297015	
16	Louver Link	9358556009	
17	Louver Shaft	9358557006	
18	Louver Link Cover	9358558010	
19	Motor Base Assy	9359067030	
20	Step Motor V	9900362010	

INDOOR UNIT
CEILING
ABYG18LVTB
ABYG22LVTA
ABYG24LVTA
Kit (flap base sub assy)

Ref.	Description	Part number	
21	Kit (Flap Base Sub Assy)	9372670040	
22	Flap Base	9358537022	
23	Protect Cover	9358564011	
24	Louver	9358561027	
25	Bushing B	9358554005	
26	Louver Stopper	9358555002	
27	Louver Rod	9358559017	
28	Motor Rod	9358560013	









Ref.	Description	Part number
41	Kit (Drain Pan Sub Assy)	9372669013
42	Drain Cap	9358746004
43	Drain Hose Assy	9377785060
44	Hose Band	9379757003
45	Evaporator Sub Assy (18)	9359051275
46	Evaporator Sub Assy (22 24)	9359051268

INDOOR UNIT
CEILING
ABYG18LVTB
ABYG22LVTA
ABYG24LVTA
Base sub assy
Control box




Ref.	Description	Part number	
51	Cap	9358563007	
52	Arm	9358565001	
53	Main PCB (ABYG18)	9709245361	
53	Main PCB (ABYG22)	9709245507	
53	Main PCB (ABYG24)	9709245378	
54	Power Supply PCB	9707398274	
55	Terminal 3P	9306489045	
56	Terminal 3P	9703345012	
57	Pipe Thermistor	9900022020	
58	Room Thermistor	9703299087	



INDOOR UNIT SLIM DUCT ARYG18LLTB



Ref	Description	Parts number	
1	Side Panel R Sub Assy	9379906012	
2	Side Panel L Sub Assy	9379907019	
3	Pipe Panel Sub Assy	9379900003	
4	Panel (Window) Sub Assy	9379915007	
5	Outlet Frame Assy	9380042013	
6	Front Panel (3 Fan)	9380595007	
7	Valve Cover Sub Assy	9379576017	
8	Fan Guard (3 Fan)	9380590002	
9	Air Filter	9379575003	
10	Main Panel (3 Fan)	9380603016	
11	Cabinet Panel (3 Fan)	9380598008	
12	Drain Pan Sub Assy	9379901178	
13	Evaporator Sub Assy	9364499833	



INDOOR UNIT
SLIM DUCT
ARYG18LLTB

Ref	Description	Parts number
21	Top Panel Sub Assy	9379908047
22	Sirroco Fan Assy	9379570022
23	Sirroco Fan Assy	9379570039
24	Shaft Assy	9381052004
25	Joint Assy	9378038011
26	Rubber (Vibration Proof)	9379644006
27	Casing B	9379572019
28	Casing U	9379571012
29	Fan Motor Assy	9602968022
30	Drain Pump Sub Assy	9379914055
31	Float Switch Sub Assy	9378593022
32	Drain Hose Assy	9379913003
33	Hose Sub Assy	9378450097


INDOOR UNIT
SLIM DUCT
ARYG18LLTB




Ref	Description	Parts number	
41	Power Supply PCB	9707398267	
42	Main PCB	9709245316	
43	Reactor Assy	9707457018	
44	Terminal 3P	9306489045	
45	Terminal 3P (Wired Remote)	9703345012	
46	Wired Remote Control	9318593013	
47	Room Thermistor	9900653019	
48	Pipe Thermistor	9900881016	

INDOOR UNIT
DUCT
ARYG22LMLA
ARYG24LMLA

Hook metal



Ref.	Description	Part number	
1	Remote Control	9318593013	



Ref.	Description	Part number	
11	Main PCB (ARYG22)	9709245491	
11	Main PCB (ARYG24)	9709245323	
12	Power Supply PCB	9707398373	
13	Terminal 3P	9703345012	
14	Terminal 3P	9306489045	
15	Reactor Assy	9707457018	
16	Room Thermistor	9900826024	
17	Pipe Thermistor	9900814014	

Bracket pipe sub assy

Main panel sub assy

INDOOR UNIT
DUCT
ARYG22LMLA
ARYG24LMLA

22

21

Ref.	Description	Part number	
21	Drain Pan Sub Assy	9374513017	
22	Evaporator Total Assy	9374517268	


INDOOR UNIT
DUCT
ARYG22LMLA
ARYG24LMLA

Intake cover sub assy

Intake frame assy


Ref.	Description	Part number	
31	Casing A	9374233021	
32	Casing B	9374234028	
33	Sirocco Fan Assy	9356531060	
34	Fan Motor Assy	9380718031	
35	Rubber	9385102002	




Motor bracket



DECORATION PANEL
UTG-UFYD-W

INDOOR UNIT
AUYG18LVLB
AUYG22LVLA
AUYG24LVLA






DECORATION PANEL
UTG-UFYD-W

Ref.	Description	Part number	
1	Connector Cover	9375549015	
2	Display Panel	9375529123	
3	Receiver Window	9375547011	
4	Indicator PCB	9707371031	
5	Decoration Panel	9375525040	
6	Panel Insulation A	9375526016	
7	Panel Insulation B	9375527013	
8	Panel Cover	9375530013	

DECORATION PANEL
UTG-UFYD-W
Intake grille assy



Ref.	Description	Part number	
11	Intake Grille	9375531034	
12	Long Life Filter	9375533014	
13	Hook Bracket	9375546014	
14	Grille Hook	9375532024	

DECORATION PANEL
UTG-UFYD-W
Flap total assy
Motor holder assy

21

22

23

24

25

Motor holder assy A


Motor holder assy B
(connector : red)

(connector : white)


Ref.	Description	Part number
21	Flap Total Assy	9377760029
22	Gear A	9375536015

Ref.	Description	Part number
21	Flap Total Assy	9377760029
22	Gear A	9375536015
23	Motor Holder	9375535018
24	Step Motor	9900139070
25	Step Motor	9900139087


INDOOR UNIT
CASSETTE
AUYG18LVLB
AUYG22LVLA
AUYG24LVLA



Ref.	Description	Part number	
1	Remote Control	9379219006	
2	Remote Control Holder	9305642045	
3	Pipe Thermistor	9900814007	
4	Room Thermistor	9900826000	
5	Main PCB (AUYG18)	9709245446	
5	Main PCB (AUYG22)	9709245514	
5	Main PCB (AUYG24)	9709245453	
6	Power Supply PCB	9707398380	
7	Terminal	9306489045	
8	Terminal	9703345012	




Ref.	Description	Part number	
11	Wire Cover	9375516017	
12	Pipe Cover	9375515010	
13	Bellmouth	9375503017	
14	Thermistor Holder	9375477011	
15	Drain Pan Sub Assy (18)	9377765024	
15	Drain Pan Sub Assy (22, 24)	9377765017	
16	Drain Port Sub Assy	9375718015	
17	Float Switch Sub Assy	9375721039	
18	Drain Pump Sub Assy	9375717025	




INDOOR UNIT
CASSETTE
AUYG18LVLB

AUYG22LVLA
AUYG24LVLA

Ref.	Description	Part number
21	Evaporator Sub Assy	9375720094
22	Insulation Box Sub Assy	9377764065
23	Evaporator Sub Assy	9375720261
24	Insulation Box Sub Assy	9377764058





22




Separate wall




Evaporator holder 2 row



24




Separate wall




Evaporator
holder 3 row




21




23



Cabinet B sub assy





Top plate assy



Motor wire holder




Cabinet A sub assy



31

32



33

Turbo fan washer



35


34

INDOOR UNIT
CASSETTE
AUYG18LVLB
AUYG22LVLA
AUYG24LVLA



Ref.	Description	Part number	
31	Fan Motor Sub Assy	9375719012	
32	Fan Motor	9602436019	
33	2 Stage Turbo Fan Assy	9375480011	
34	Shaft Cap	9377807014	
35	Washer Cover	9377811011	


ACCESSORIES


OUTDOOR UNIT

Name and Shape	Q'ty	Use
Drain pipe 	1	For drain piping work 9303029015
Drain cap 	2	313166024302
One-touch bush 	2	For power supply cable and connection cable installation

INDOOR UNIT
CEILING
ABYG18LVTB
ABYG22LVTA
ABYG24LVTA


Name and Shape	Q'ty
Cover plate (Left) 	1
Cover plate (Right) 	1
Screw (M4 × 10mm) 	2
Installation template  Positioning for under ceiling type	1
Bracket (Left)  For suspending the indoor unit from ceiling	1
Bracket (Right)  For suspending the indoor unit from ceiling	1



Name and Shape	Q'ty
Special nut  For suspending the indoor unit from ceiling	4
Wall bracket  For suspending the indoor unit on the wall	2
Screw (M4 × 20mm)  For fixing the wall bracket	6
Coupler heat insulator (Large)  For indoor side pipe joint(Large pipe)	1
Coupler heat insulator (Small)  For indoor side pipe joint (Small pipe)	1
Binder (Large)  For fixing drain hose	1


Name and Shape	Q'ty
Binder (Small)  For electrical wiring	2
Wire clammer  For electrical wiring	1
Drain hose  	1
Hose band  For installing drain hose	1
Insulation (Drain hose)  Adhesive type 100 x 220(mm)	1
VT wire  For fixing drain hose L 280mm	1

Name and Shape	Q'ty
Remote control 	1
Battery  For remote control	2
Remote control holder 	1
Screw (M3 × 12mm)  For remote control holder installation	2



INDOOR UNIT
SLIM DUCT
ARYG18LLTB




Name and Shape	Q'ty
Installation template  For positioning the indoor unit	1
Washer  For installing indoor unit	8
Coupler heat insulation (Large)  For indoor side pipe joint	1
Coupler heat insulation (Small)  For indoor side pipe joint	1
Cable tie (Medium)  For power supply and remote control cable binding	3


Name and Shape	Q'ty
Cable tie (Large)  For fixing the coupler heat insulation	4
Filter (Large) 	2
Drain hose  For installing drain pipe VP25 (O.D.32 I.D.26)	1
Hose band  For installing drain hose	1
Drain hose insulation B  Insulates the drain hose	1

Name and Shape	Q'ty
Wired remote control 	1
Remote control cable  For connecting the remote control	1
Tapping screw (M4 x 16 mm)  For installing the remote control	2




INDOOR UNIT
DUCT
ARYG22LMLA
ARYG24LMLA




Name and Shape	Q'ty
Hanger  For suspending the indoor unit from ceiling	4
Drain hose insulation  Insulates the drain hose and vinyl hose	1
Cable tie (Large)  For fixing drain hose	1
Cable tie (Small)  For remote control and remote control cable binding	1
Cable tie  For electrical wiring	2

Name and Shape	Q'ty
Wire clammer  For electrical wiring	1
Remote control  For air conditioner operation	1
Remote control cable  For connecting the remote control	1
Screw (M4 × 16)  For installing the remote control	2
Coupler heat insulation (Large)  For indoor side pipe joint (gas)	1




Name and Shape	Q'ty
Coupler heat insulation (Small)  For indoor side pipe joint (liquid)	1
Special nut A (Large flange)  For suspending the indoor unit from ceiling	4
Special nut B (Small flange)  For suspending the indoor unit from ceiling	4

INDOOR UNIT
CASSETTE
AUYG18LVLB
AUYG22LVLA
AUYG24LVLA

Name and Shape	Q'ty
Coupler heat insulation (Large)  For indoor side pipe joint (gas pipe)	1
Coupler heat insulation (Small)  For indoor side pipe joint (liquid pipe)	1
Special nut A (Large flange)  For installing indoor unit	4
Special nut B (Small flange)  For installing indoor unit	4
Template (Carton top)  For cealing openings cutting Also used as packing	1
Drain hose  For installing drain pipe	1
Hose Band  For installing drain hose	1

Name and Shape	Q'ty
Drain hose insulation  For installing drain pipe	1
Remote control  	1
Battery  	2
Remote control holder  	1
Tapping screw (M3 × 12mm)  Mounting the remote control holder	2
Cable tie  For electrical wiring	2
Wire clamber  For electrical wiring	1

DECORATION PANEL
UTG-UFYD-W

Name and Shape	Q'ty
Connector cover  For covering connector	1
Tapping Screw (M5 × 12 mm)  Mounting decoration panel	4
Tapping Screw (M4 × 12 mm)  Mounting connector cover	1
L angle  Mounting the Hook Wire to the decoration panel	2
Hook wire  Suspending the decoration panel	2
Screw [pitch small] (M4 × 10 mm)  Mounting the Hook wire (for metals)	2
Screw [pitch large] (M4 × 10 mm)  Mounting the L angle and Hook wire (for resins)	4

1601G4482